

SPALDING®

**LynRus QR3000
Model # 402-742**

SPALDING SPECIFICATIONS

DATE: 01/01/06

MODEL NUMBER: 402742

DESCRIPTON: LYNRUS QR3000 3/4HP ELECTRIC WINCH

SPECIFICATIONS:

Lightweight unit, only 68 pounds/30.84 kilograms.

A powerful, instantly reversing 3/4 HP motor is governed to stall at 14 amps to prevent overload. It develops over 1,000 pounds/453.51 kilograms of line pull at a speed of 9 feet/2.74 meters per minute.

A large grooved drum, with a 4-1/2 inch/11.42 centimeter diameter, assures long cable life and proper coiling.

A hardened steel worm gear is supported for both radial and thrust loads, unlike winches that use an unsupported high-speed gear that can create a great strain on the motor, shortening its life.

Positive locking, the double reduction worm gear drive provides a 200:1 reduction rate that creates a strong cable hold under load. This eliminates the need for special brakes that can overload the motor, causing it to generate excessive heat and shorten its life.

Sealed gear case uses precision ground bearings and premium seals for superior performance and a lifetime of maintenance-free operation.

Can be mounted in any position for flexibility during installation.

Extensive Life Cycle testing assures high quality and long life.

The winch contains a 6' 14/4 power cord with a strain relief at the box and a 4 prong twist lock plug as per NEMA L14-20P. There will also be a 4 prong twist lock receptacle per NEMA L14-20R and 812 cover for a 4" square electrical box for use with the receptacle during installation.

Each unit shall be accompanied with a key switch and electrical box cover.

UL Listed.

Five year limited warranty.